

| | Type | Hits | Search Text | DBs | Time Stamp | Comments | Error Definitio |
|---|------|------|--|--|---------------------|----------|--------------------|
| 1 | BRS | 2509 | 702/57,64,69,81,84,189,190 ,191,193,for.103,for.104,f or.105,for.106,for.155,for .160.ccls. | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:49 | | |
| 2 | BRS | 2439 | 330/267,268,288,290,296.cc ls. | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:50 | | |
| 3 | BRS | 1793 | 327/538,540,547.ccls. | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:50 | | |
| 4 | BRS | 2183 | 323/312,313,314,315,317.cc ls. | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:51 | | |
| 5 | BRS | 0 | (determin\$3 or measur\$3) with current with driver adj curcuitry | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:31 | | |
| 6 | BRS | 21 | (determin\$3 or measur\$3) with current with driver adj circuitry | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:32 | | |

| | Type | Hits | Search Text | DBs | Time Stamp | Comments | Error Definiti on |
|----|------|------|---|--|---------------------|----------|-------------------------|
| 7 | BRS | 0 | (determin\$3 or measur\$3) with current with driver adj circuitry and impedance with reference | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:32 | | |
| 8 | BRS | 4 | (determin\$3 or measur\$3) with current with driver adj circuitry and impedance | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:35 | | |
| 9 | BRS | 0 | accurate with (determin\$5 or measur\$5) with suppl\$3 with current and driver adj circuitry and impedance | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:37 | | |
| 10 | BRS | 64 | accurate with (determin\$5 or measur\$5) with suppl\$3 with current and impedance | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:37 | | |
| 11 | BRS | 14 | accurate with (determin\$5 or measur\$5) with suppl\$3 with current and impedance with (reference or predetermin\$3 or preddefin\$2 or preset\$4 or threshold\$1) | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:38 | | |
| 12 | BRS | 2799 | 702/57,64,69,81,84,189,190 ,191,193,for.103,for.104,f or.105,for.106,for.155,for .160.ccls. | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:50 | | |

| | Type | Hits | Search Text | DBs | Time Stamp | Comments | Error Definiti on |
|----|------|------|--|--|---------------------|----------|-------------------------|
| 13 | BRS | 2499 | 330/267, 268, 288, 290, 296.ccl ls. | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:50 | | |
| 14 | BRS | 1890 | 327/538, 540, 547.ccl ls. | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:50 | | |
| 15 | BRS | 2273 | 323/312, 313, 314, 315, 317.ccl ls. | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:58 | | |
| 16 | BRS | 0 | measur\$5 with cuppl\$3 with current with (driver or integrated) with circuit\$2 | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:59 | | |
| 17 | BRS | 443 | measur\$5 with suppl\$3 with current with (driver or integrated) with circuit\$2 | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 10:59 | | |

| Type | Hits | Search Text | DBs | Time Stamp | Comments | Error Definiti on |
|--------|------|--|---|------------|----------|-------------------------|
| 18 BRS | 0 | measur\$5 with suppl\$3 with current with (driver or integrated) with circuit\$2 and compar\$4 with termination with impedance with (reference\$1 or threshold\$1 or predetermin\$3 or preset\$4 or predefin\$2) | USPAT; US-PGPUB; EPO; 2004/02/26 JPO; DERWENT; 11:01 IBM_TDB | | | |
| 19 BRS | 6 | measur\$5 with suppl\$3 with current with (driver or integrated) with circuit\$2 and compar\$4 with impedance with (reference\$1 or threshold\$1 or predetermin\$3 or preset\$4 or predefin\$2) | USPAT; US-PGPUB; EPO; 2004/02/26 JPO; DERWENT; 11:01 IBM_TDB | | | |
| 20 BRS | 325 | current with measur\$5 with precision with resistor\$1 | USPAT; US-PGPUB; EPO; 2004/02/26 JPO; DERWENT; 11:11 IBM_TDB | | | |
| 21 BRS | 2 | current with measur\$5 with precision with resistor\$1 and compar\$4 with impedance with (reference\$1 or threshold\$1 or predetermin\$3 or preset\$4 or predefin\$2) | USPAT; US-PGPUB; EPO; 2004/02/26 JPO; DERWENT; 11:13 IBM_TDB | | | |

| | Type | Hits | Search Text | DBs | Time Stamp | Comments | Error Definiti on |
|----|------|------|--|--|---------------------|----------|-------------------------|
| 22 | BRS | 20 | current with measur\$5 with precision with resistor\$1 and impedance with (reference\$1 or threshold\$1 or predetermin\$3 or preset\$4 or predefin\$2) | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 11:13 | | |
| 23 | BRS | 114 | core adj power and supply adj power | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 14:24 | | |
| 24 | BRS | 10 | core adj power with supply adj power | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB | 2004/02/26 14:24 | | |